This is a 22 CONTROLLED DOCUMENT

EG&G - ROCKY FLATS PLANT ENVIRONMENTAL MANAGEMENT

This is a RED Stamp

ROCKY FLATS PLANT EMD OPERATING PROCEDURES MANUAL

Manual No.: Procedure No.:

Procedure No. Page:

Effective Date:

5-21000-OPS-GT Table of Contents, Rev 32

1 of 3

01/05/93

Organization: Environmental Management

THIS IS ONE VOLUME OF A SIX VOLUME SET WHICH INCLUDES:

VOLUME I: FIELD OPERATIONS (FO)
VOLUME II: GROUNDWATER (GW)
VOLUME III: GEOTECHNICAL (GT)
VOLUME IV: SURFACE WATER (SW)
VOLUME V: ECOLOGY (EE)
VOLUME VI: AIR (AP)

TABLE OF CONTENTS FOR VOLUME III: GEOTECHNICAL

Procedure <u>No.</u>	Title	Rev. No.	Effective <u>Date</u>
GT.01	Logging Alluvial and Bedrock Material	2	05/12/92
DCN 92.01	Specialized Logging Form	2	11/13/92
GT.02	Drilling and Sampling Using Hollow Stem Auger Techniques	2	05/12/92
DCN 92.01	Superseded by DCN 92.03	2	07/27/92
DCN 92.02	Superseded by DCN 92.03	2	07/27/92
DCN 92.03	Addition ot the Drum Characterization	2	07/27/92
DCN 92.04	Prevention of Down Hole Contamination	2	08/26/92
DCN 92.05	Field Modification	2	12/04/92
GT.03	Isolating Bedrock from Alluvium with Grouted Surface Casing	2	05/12/92
DCN 92.03	Expired	2	09/03/92
GT.04	Rotary Drilling and Rock Coring	2	05/12/92

ROCKY FLATS PLANT EMD OPERATING PROCEDURES MANUAL Manual No.: Procedure No.: Page:

Effective Date: Organization:

5-21000-OPS-GT Table of Contents, Rev 32

2 of 3 01/05/93

Environmental Management

Procedure No.	Title	Rev. <u>No.</u>	Effective <u>Date</u>
GT.05	Plugging and Abandonment of Boreholes	2	05/12/92
DCN 92.01	Field Modification	2	12/09/92
GT.06	Monitoring Wells and Piezometer Installation	2	05/12/92
DCN 92.05	Schematic Diagram Land Fill Methane Wells	2	06/04/92
DCN 92.06	Field Modification	2	11/12/92
DCN 92.07	Provide Consistency	2	12/17/92
*DCN 93.01	Borehole Advancement	2	01/04/93
GT.07	Logging and Sampling of Test Pits and Trenches	2	05/12/92
GT.08	Surface Soil Sampling	2	05/12/92
DCN 92.01	Clarification of Soil Sampling	2	09/03/92
DCN 92.02	Consistency Change	2	10/12/92
*DCN 93.01	Work Plan Consistency	2	01/05/93
GT.09	Soil Gas Sampling and Field Analysis	2	05/12/92
GT.10	Borehole Clearing	2	05/12/92
GT.11	Plugging and Abandonment of Wells	2	05/12/92
GT.15	Geophysical Borehole Logging	2	05/12/92
GT.17	Land Surveying	2	05/12/92
GT.18	Surface Geophysical Surveys	2	05/12/92
DCN 92.01	Surface Magnetic Surveys Procedure	2	09/30/92
DCN 92.02	Modification to Stacking Requirements	2	10/15/92

ROCKY FLATS PLANT EMD OPERATING PROCEDURES MANUAL Manual No.: Procedure No.:

5-21000-OPS-GT Table of Contents, Rev 32

Page:

3 of 3

Effective Date:

01/05/93

Organization:

Environmental Management

Procedure <u>No.</u>	<u>Title</u>	Rev. No.	Effective Date
DCN 92.03	Modification to Method of Taking Readings	2	10/15/92
GT.19	Field Gas Chromatographs	2	05/12/92
GT.20	Procedures for Soil Interstitial Water Sampling and Sampler Installation	2	05/12/92
GT.21	Cone Penetrometer Testing	1	05/12/92
GT.24	Approval Process for Construction Activities on or Near Individual Hazardous Substance Sites (IHSSs)	0	05/12/92

This is a 22 CONTROLLED DOCUMENT EG&G - ROCKY FLATS PLANT ENVIRONMENTAL MANAGEMENT This is a RED Stamp

ENVIRONMENTAL MANAGEMENT DOCUMENT CHANGE NOTICE (DCN)

Procedure Number 5-51000-OPS-GT.6, Rev2

Page 1 of 1

Title M	IONITOR	ING WELLS AI	ND PIEZOMET	ER INSTALLA	ATION	Date <u>11/12/92</u>	DCN Numb 5-21000-0	جهري per 9 3.0 PS- GT.6,Rev2
Expires _	-11/12/	2 12/10/9	ده	Procedure Re	vision Required		<u> </u>	
Scope Li	mitation	Operable	Unit No. 5	·····			· · · · · · · · · · · · · · · · · · ·	
Item Number	Page	Step or Paragraph	Changes (Use DCN CONTINUATION SHEET for Additional Space)					
1	6	1	Change the second sentence to read:			_ 		
2	† 11	2	Therefore, after the augers have been advanced to the bedrock contact, an appropriately-sized drive sampler will be driven 2 to 5 feet into the claystone bedrock to provide a pilot hole, no more than 1 inch greater than the outside diameter (O.D.) of the casing, for a 2-foot deep sediment sump and to classify the bedrock lithology below the contact. Add the following to the end of the second paragraph: Before placing the well assembly into the borehole, any void space/between the bottom of the borehole and the bottom of the sediment sump will be backfilled with commercially available bentonite pellets.					
The bo	reholes (i) (·	ding items Above) ਜਨਪਾਦ ਸਿਖ਼ ਸਿਵਾਦ ਨਿ ਜਹ ਨ	uidstone will	ili s
Concur	rence	Organization	Req	Date	Concurrent	e Organization	Req	Date
M	59	MILOAPM	Х	14/4/5	5 Cmar	User	X	11/13/92
		!						
Approval	of Respo	onsible Manger	Date ///3	3/92	Is Posting Re			Date Posted
CHYSION AST			/	1	· · · · · · · · · · · · · · · · · · ·		DJ SA	1110